



**JOINT DETAIL**  
 RUBBER GASKET PER  
 ASTM C-443  
 BUTLY RUBBER GASKET  
 PER ASTM C-990

**SECTION WITH SLAB TOP**

- NOTES:**
1. 4000 PSI CONCRETE AT 28 DAYS.
  2. RISERS, CONES AND SLABS IN ACCORDANCE WITH ASTM C-478, LATEST REVISION.
  3. INVERT LOCATION TO WITHIN A TOLERANCE OF +/- 1INCH.
  4. ANY DEVIATION FROM THIS DRAWING MUST BE MADE TO GSP IN WRITING PRIOR TO PRODUCTION.
  5. STEEL REINFORCED COPOLYMER STEPS AT 12" O.C. STARTING 30" OFF FLOOR.

SAN-1

SEPTEMBER 2019

SHEET <b>1</b> OF <b>1</b>	<b>WEIGHT</b> 6" BASE = 1,375 LBS PER VERTICAL FOOT = 867 LBS 6" TOP SLAB = 1,111 LBS	<b>PRECAST</b> <b>48" DIAMETER MANHOLE</b> <b>ASSEMBLY-SANITARY</b>	<b>GARDEN STATE PRECAST</b> <b>FARMINGDALE, N.J.</b> <b>PHONE #: 732-938-4436 FAX #: 732-938-7096</b>
-------------------------------	--	---	---